# AB80J/AB85J

### **ARTICULATED BOOM LIFTS**



- The ultimate diesel articulated booms
- Excellent aerial maneuverability with "up & over" capabilities
- Powerful 4-wheel drive and 4-wheel steer
- Smooth, precise, easy to use controls
- Simple to maintain and service



### ARTICULATED BOOM LIFTS


DIMENSIONS	AB80J	AB85J
Max. working height	85 ft 11 in	90 ft 6 in
Max. platform height	79 ft 11 in	84 ft 6 in
Max. horizontal reach	59 ft 5 in	61 ft 11 in
Clearance height at max. outreach	27 ft 11 in	27 ft 11 in
Platform size	8 ft x 3 ft	8 ft x 3 ft
Overall width ( <b>A</b> )	8 ft 6 in	8 ft 6 in
Overall length ( <b>B</b> )	32 ft 2 in	41 ft 2 in
Stowed height ( <b>C</b> )	9 ft 10 in	9 ft 10 in
Ground clearance	13 in	13 in

PERFORMANCE			
Platform capacity (SWL)	500 lbs	500 lbs	
Max. wind speed	28 mph	28 mph	
Max. drive height	79 ft 11 in	84 ft 6 in	
Max. drive speed (stowed)	3.0 mph	3.0 mph	
Max. drive speed (elevated)	0.6 mph	0.6 mph	
Jib length	5 ft	6 ft 6 in	
Jib arc	140°	135°	
Jib rotation	n/a	140° side to side	
Platform rotation	150°	150°	
Superstructure rotation (continuou	ıs) 360°	360°	
Tailswing	35 in	35 in	
Raise/lower time	240/240 sec	240/240 sec	
Gradeability	30%	30%	
Inside turning radius	7 ft 10 in	7 ft 10 in	
Outside turning radius	15 ft 5 in	15 ft 5 in	
Tires		15 x 625 foam filled	
Controls	proportional joystick		
Drive system	4-wheel drive		


POWER	
Power source	Kubota V2403 65hp diesel - Tier 4 Final

WEIGHT		
Weight	36,800 lbs	38,580 lbs

#### **WORKING ENVELOPE**



## AB80J/AB85J



#### STANDARD FEATURES

- Snorkel Guard™ secondary guarding system
- Hydraulic platform rotation
- 4-wheel drive, steer and crab steer
- Foam filled tires
- Proportional drive, lift & swing, extend & rotate
- Drive motion alarm
- Flashing amber light
- Horn
- Dual lanyard attachment points
- Power line to platform
- 3.5° tilt alarm
- 2 year parts & labor, 5 year structural warranty
- ANSI compliant

#### **OPTIONS**

- Special paint colors
- Airline to platform
- Non-marking tires
- AC generator 110V/240V 2kW
- Aircraft package
- Deluxe aircraft package
- Cold weather package
- Extreme cold weather package
- Extreme environment package
- Light package
- Tow kit
- Glazier package
- Utility package
- Pipe rack
- 12kW generator package
- 12kW generator/welder package
- Dual fuel
- Environmental hydraulic oil
- Tool tray
- Personal fall arrest system
- Snorkel OnSite™ telematics

**S**snorkel

P.O. Box 1160

St.Joseph, MO 64502-1160, USA

Tel: 1 (785) 989-3000

Toll-free: 1 (800) 255-0317 Fax: 1 (785) 989-3070

Email: sales.usa@snorkellifts.com